



## WATER-BASED CLEAR SACRIFICIAL NANOSTRUCTURED COMPOUND

### Product Description


**PoreKote AG** is a clear, one-component, sacrificial, ready-to-use coating intended for use over previously painted concrete. It is self-crosslinking and offers excellent graffiti resistance and cleanability with domestic water jet. **PoreKote AG** is suitable for exterior & interior building surfaces and shows resistance against UV.

### Fields of Application

**PoreKote AG** is suitable for the graffiti protection of vertical painted surfaces.

- Acrylic wall paint
- Emulsion paint

### Properties-Advantages



- Graffiti removal just with water
- Yellowing resistant
- Does not change the original appearance of the surface
- Solvent-free, VOC-free and PFOA-free (does not contain toxic substances)
- Ready-to-use
- Easy to apply
- Resistant to temperatures up to +70°C



## WATER-BASED CLEAR SUCRIFICIAL NANOSTRUCTURED COMPOUND

### Technical Characteristic

Appearance/Color	Milky white liquid
Density (EN ISO 2811.01)	1.01 kg/l
Consumption	200ml/m <sup>2</sup> (applied in 2 layers, 100ml/m <sup>2</sup> per layer)
Drying time (25°C, 65% RH)	1 hour
Recoating time (25°C, 65% RH)	1 hour
Full cure time (25°C, 65% RH)	24 hours

### Application Condition

Relative atmospheric humidity	< 80%
Surface humidity content	< 4%
Application temperature	+5°C to +45°C

### Instructions for use

**Surface preparation:** Clean the surface from dust, mildew, dirt or any poorly adhering material. Use mechanical means or water blasting to clean the substrate. Avoid the use of detergents or soap, as they affect the adhesion of the product to the surface.

**Application:** **PoreKote AG** is ready for use. Apply two layers on a dry surface with a brush, roller, or spray gun, working from the lower to the higher part of the vertical surfaces.

**When the temperature is higher than +35°C / mist water (30g tap water/m<sup>2</sup>) on the surface and after 5 minutes apply the **PoreKote AG**.**

#### Consumption rate:

Polished surfaces:	150ml/m <sup>2</sup>
Painted wall:	200ml/m <sup>2</sup>
Concrete:	300-400ml/m <sup>2</sup>

### Packaging

5 LITRES - 20 LITRES - 200 LITRES

### Cleaning of Tools

Use tap water

### Storage Stability

**PoreKote AG** is stable for 24 months when kept unopened in its original container, protected from frost and direct sunlight

Tel: (+973) 1782 2069 • Fax: (+973) 1782 2269 • [www.basichem-me.com](http://www.basichem-me.com)